



PVC PROTECTION TAPE (BLACK)

DATE OF TEST : 18/1/2017

ADHESIVE	TAPE COLOR(T) & RELEASE LINER (R.)	FORCE (N)	ELONGATION (%)	TOTAL THICKNESS (MM)
Natural rubber	Black	1	150	0.110 ± 0.005

INITIAL TACK (# 7)	PEEL ADHESION (180°) (N /INCH)	TENSILE STRENGTH (N/CM)	HOLDING POWER (PER HOUR)	HEAT RESISTING (MINUTE / °C)
≥10	1	16	----	30MIN

(# = BALL) (UM = MICRON) (°C = CELSIUS) (≥ = GREATER THAN) (≤ = LESS THAN) (% = PERCENT) (N=NEWTON)

SHELF LIFE :

12 Month storage at 23°C and 65% Relative Humidity

GENERAL DESCRIPTION :

PVC protection tape features a rubber based pressure sensitive adhesive which adheres well to both glass and aluminium for external applications . The product has a medium tack which provides a stable adhesive strength yet removes cleanly without leaving residue . Perfect for protecting metal surfaces during transportation , installation and construction .

APPLICATIONS :

Used extensively in the aluminium window and door industry Nationwide .

Note : All information and recommendations are given by us in good faith on the basis of practical experience, but without warranty . The user shall determine the suitability of the product and the method of application for each specific use.

IDEALTAPE SDN BHD (969219-X)

NO : 7 JALAN BALAKONG JAYA 1 , TAMAN INDUSTRI BALAKONG JAYA , 43300 BALAKONG SELANGOR DARUL EHSAN , MALAYSIA .

TEL : 03-8964 0983 / 016-2100 268 FAX : 03-8964 0982 EMAIL : idealtapesb@gmail.com

WEBSITE : www.idealteape.com.my